

LamiTAG-E



Product Specification:

Type	Thickness (mm.)	Light Performances			Energy Performances						U Value		
		EN			EN	ISO	NFRC	EN	ISO	NFRC	EN	ISO	NFRC
		LT (%)	LR Out (%)	LR In (%)	SF (%)	SHGC (%)	SC			W/(m ² .K)		U-Summer W/(m ² .K)	
* LAMITAG-E Clear (6+0.76+6)	12.76	71	16	14	0.52	0.52	0.53	0.60	0.60	0.60	5.41	5.45	5.51
LAMITAG-E Green (6+0.76+6)	12.76	59	11	16	0.44	0.45	0.48	0.51	0.52	0.55	5.41	5.45	5.51
LAMITAG-E Sky Blue (6+0.76+6)	12.76	46	8	16	0.42	0.44	0.47	0.49	0.50	0.54	5.40	5.44	5.51
LAMITAG-E Euro Bronze (6+0.76+6)	12.76	41	7	16	0.42	0.43	0.47	0.48	0.50	0.53	5.41	5.45	5.51
LAMITAG-E Euro Grey (6+0.76+6)	12.76	36	7	16	0.40	0.42	0.45	0.46	0.48	0.52	5.40	5.44	5.51
LAMITAG-E Blue Green (6+0.76+6)	12.76	50	9	16	0.42	0.43	0.46	0.48	0.49	0.53	5.40	5.44	5.51
LAMITAG-E Energy Green (6+0.76+6)	12.76												

* LE clear glass (outer pane), Clear glass (inner pane)
 Tinted glass (outer pane), LE clear glass (inner pane)