

## SolarTAG Plus



### Product Specification:

Type	Thickness (mm.)	Light Performances			Energy Performances						U Value		
		EN			EN	ISO	NFRC	EN	ISO	NFRC	EN	ISO	NFRC
		LT (%)	LR Out (%)	LR In (%)	SF (%)	SHGC (%)	SC			W/(m <sup>2</sup> .K)		U-Summer W/(m <sup>2</sup> .K)	
SOLARTAG Plus on Clear - CS 114	6	15	33	36	0.24	0.25	0.28	0.28	0.29	0.32	4.57	4.59	4.59
	8	15	32	36	0.24	0.25	0.28	0.28	0.29	0.32	4.53	4.56	4.55
SOLARTAG Plus on Clear - CS 120	6	22	25	29	0.31	0.32	0.35	0.35	0.37	0.40	4.83	4.87	4.89
	8	21	25	29	0.31	0.32	0.35	0.35	0.36	0.40	4.79	4.82	4.84
<b>SOLARTAG Plus on Clear - CS 130</b>	6	<b>33</b>	<b>19</b>	<b>26</b>	<b>0.42</b>	<b>0.43</b>	<b>0.46</b>	<b>0.48</b>	<b>0.50</b>	<b>0.53</b>	<b>5.14</b>	<b>5.18</b>	<b>5.25</b>
	8	<b>33</b>	<b>18</b>	<b>26</b>	<b>0.41</b>	<b>0.42</b>	<b>0.45</b>	<b>0.47</b>	<b>0.49</b>	<b>0.52</b>	<b>5.10</b>	<b>5.13</b>	<b>5.20</b>
SOLARTAG Plus on Green - CS 214	6	13	23	34	0.24	0.25	0.28	0.27	0.29	0.32	4.63	4.66	4.66
	8	13	22	34	0.23	0.25	0.28	0.27	0.28	0.32	4.59	4.62	4.61
SOLARTAG Plus on Green- CS 220	6	18	19	31	0.27	0.29	0.32	0.31	0.33	0.37	4.82	4.85	4.88
	8	18	18	31	0.27	0.28	0.32	0.31	0.32	0.37	4.78	4.81	4.83
SOLARTAG Plus on Sky Blue - CS 514	6	10	17	36	0.23	0.24	0.28	0.26	0.28	0.32	4.58	4.61	4.60
	8	9	14	36	0.22	0.24	0.27	0.25	0.27	0.32	4.55	4.57	4.56
SOLARTAG Plus on Sky Blue - CS 520	6	12	16	29	0.25	0.26	0.30	0.28	0.30	0.34	4.76	4.79	4.80
	8	11	13	29	0.24	0.25	0.29	0.27	0.29	0.34	4.72	4.75	4.76